

Response to Office Action
SN 10/008393
Customer No. 33354

CLAIMS

This listing will replace all prior versions of the claims in the application.

1. (original) A hand-held laser light generator device for use in medical therapy, said device comprising:

(a) a wand in the form of a substantially elongated hollow tube defining an interior cavity and capable of being retained in a hand of a user and freely moved relative to the surface of the skin of a patient to receive the medical therapy;

(b) means mounted in said interior cavity of said wand for generating a beam of laser light in the red color spectrum;

(c) an optical arrangement mounted in said interior cavity of said wand for receiving the red color spectrum generated beam of laser light from said generating means and for transforming the generated beam of laser light into a substantially planar beam of laser light disposed externally of said wand for producing a line of laser light in the red color spectrum at a desired location on the surface of the patient's skin and with said line of laser light being visible to the user as said wand is held and freely moved by the user in a spaced relationship from and out of contact with the patient;

(d) a housing defining an interior chamber and having an exterior;

Response to Office Action
SN 10/008393
Customer No. 33354

(e) means disposed in said interior chamber of said housing for supplying electrical power to said laser beam generating means;

(f) means for electrically interconnecting said laser beam generating means and said electrical power supplying means such that said wand is movable relative to said housing; and

(g) means on said housing for controlling a period of time said beam of laser light is generated.

2. (original) The device of claim 1 wherein said generating means is a semiconductor diode laser using less than one watt of power.

3. (original) The device of claim 1 wherein the generated said beam of light has a wavelength of about 635 nm.

4. (original) The device of claim 1 wherein said optical arrangement includes:

a collimating lens; and

a line generating prism, said collimating lens and line generating prism being disposed in a serial relation to said generating means.

5. (original) The device of claim 1 wherein said electrical power supplying means is a battery.

6. (original) The device of claim 1 wherein said controlling means includes:

Response to Office Action
SN 10/008393
Customer No. 33354

an electrical timing circuit disposed in said interior chamber of and being mounted to said housing;

a start switch activatable between on and off positions; and

a selector knob having multiple period of time length setting positions, said start switch and selector knob being mounted to said housing and accessible at said exterior thereof and being in operable communication with said electrical timing circuit for controlling initiation of generation of said beam of laser light and length of the period of time said beam of laser light is generated.

7. (original) The device of claim 6 wherein said controlling means further includes:

a lock mechanism mounted to said housing; and

a key for actuating said lock mechanism between a first position in which said lock mechanism permits said start switch to be activated to said on position and a second position in which said lock mechanism prevents said start switch from being activated to said on position.

8. (original) The device of claim 1 wherein said housing further has a cradle mounted to and projecting outwardly from said exterior of said housing for releasably securing said wand thereto, said cradle defining an annular slot open at opposite ends such that said tubular wand can be removably and slidably placed through said slot in a relatively tight-fitting relationship with said cradle and thereby retained by said cradle in a storage position spaced from and alongside said housing.

Response to Office Action
SN 10/008393
Customer No. 33354

9. (original) The device of claim 1 wherein said housing further has a clip mounted to said exterior of said housing for releasably securing said housing to an article of clothing worn by the user.

10. (original) A hand-held laser light generator device for use in medical therapy, said device comprising:

(a) a wand in the form of a substantially elongated hollow tube defining an interior cavity and capable of being retained in a hand of a user and freely moved relative to the surface of the skin of a patient to receive the medical therapy;

(b) a semiconductor diode laser mounted in said interior cavity of said wand for generating a beam of laser light in the red color spectrum;

(c) an optical arrangement mounted in said interior cavity of said wand for receiving the red color spectrum generated beam of laser light from said generating means and for transforming the generated beam of laser light into a substantially planar beam of laser light disposed externally of said wand for producing a line of laser light in the red color spectrum at a desired location on the surface of the patient's skin and with said line of laser light being visible to the user as said wand is held and freely moved by the user in a spaced relationship from and out of contact with the patient;

Response to Office Action
SN 10/008393
Customer No. 33354

(d) a housing defining an interior chamber and having an exterior;

(e) a battery disposed in said interior chamber of said housing for supplying electrical power to said laser;

(f) an electrical cord having opposite ends, one of said opposite ends being attached to said wand and making electrical connection with said laser, the other of said opposite ends being attached to said housing and making electrical connection with said battery such that said wand is movably relative to said housing; and

(g) means for controlling a period of time said beam of laser light is generated, said controlling means including

(i) an electrical timing circuit disposed in said interior chamber of and being mounted to said housing,

(ii) a start switch activatable between on and off positions,

(iii) a selector knob having multiple period of time length setting positions, said start switch and selector knob being mounted to said housing and accessible at said exterior thereof and being in operable communication with said electrical timing circuit for controlling initiation of generation of said beam of laser light and length of the period of time said beam of laser light is generated,

Response to Office Action
SN 10/008393
Customer No. 33354

(iv) means electrically activatable for generating a sound audible to the user, and

(v) means electrically connected to said timing circuit and said sound generating means for electrically charging in response to said beam of laser light being generated and for electrically discharging and thereby electrically activating said sound generating means in response to termination of generation of said beam of laser light.

11. (original) The device of claim 10 wherein said laser uses less than one watt of power.

12. (original) The device of claim 10 wherein said generated said beam of laser light has a wavelength of about 635 nm.

13. (original) The device of claim 10 wherein said optical arrangement includes;

a collimating lens; and

a line generating prism, said collimating lens and line generating prism being disposed in a serial relation to said laser.

14. (original) The device of claim 10 wherein said controlling means further includes:

a lock mechanism mounted to said housing; and

Response to Office Action
SN 10/008393
Customer No. 33354

a key for actuating said lock mechanism between a first position in which said lock mechanism permits said start switch to be activated to said on position and a second position in which said lock mechanism prevents said start switch from being activated to said on position.

15. (original) The device of claim 10 wherein said housing further has a cradle mounted to and projecting outwardly from said exterior of said housing for releasably securing said wand thereto, said cradle defining an annular slot open at opposite ends such that said tubular wand can be removably and slidably placed through said slot in a relatively tight-fitting relationship with said cradle and thereby retained by said cradle in a storage position spaced from and alongside said housing.

16. (original) The device of claim 10 wherein said housing further has a clip mounted to said exterior of said housing for releasably securing said housing to an article of clothing worn by the user.

17. (original) A hand-held laser light generator device for use in medical therapy, said device comprising:

(a) a wand in the form of a substantially elongated hollow tube defining an interior cavity and capable of being retained in a hand of a user and freely moved relative to the surface of the skin of a patient to receive the medical therapy;

Response to Office Action
SN 10/008393
Customer No. 33354

(b) a semiconductor diode laser mounted in the interior cavity of said wand and using less than one watt of power for generating a beam of laser light in the red color spectrum and having a wavelength of about 635 nm;

(c) an optical arrangement mounted in said interior cavity of said wand and including

(i) a collimating lens, and

(ii) a line generating prism, said collimating lens and line generating prism being disposed in a serial relation to said laser such that said beam of laser light in said red color spectrum generated by said laser is received and transformed into a substantially planar beam of laser line disposed externally of said wand for producing a line of laser light in the red color spectrum at a desired location on the surface of the patient's skin and with said line of laser light being visible to the user as said wand is held and freely moved by the user in a spaced relationship from and out of contact with the patient;

(d) a housing defining an interior chamber and having an exterior;

(e) a battery disposed in said interior chamber of said housing for supplying electrical power to said laser;

(f) an electrical cord having opposite ends, one of said opposite ends being attached to said wand and making electrical connection with said laser, the other of said opposite ends being

Response to Office Action
SN 10/008393
Customer No. 33354

attached to said housing and making electrical connection with said battery such that said wand is movable relative to said housing; and

(g) means on said housing for controlling a period of time said beam of laser light is generated, said controlling means including

(i) an electrical timing circuit disposed in said interior chamber of and being mounted to said housing,

(ii) a push button start switch activatable between on and off positions,

(iii) a rotary selector knob having multiple period of time length setting positions, said push button start switch and rotary selector knob being mounted to said housing and accessible at said exterior of said housing and being in operable communication with said electrical timing circuit for controlling initiation of generation of and length of the period of time said beam of laser light is generated,

(iv) a lock mechanism mounted to said housing,

(v) a key for actuating said lock mechanism between a first position in which said lock mechanism permits said push button start switch to be activated to said on position and a second position in which said lock mechanism prevents said push button start switch from being activated to said on position,

Response to Office Action
SN 10/008393
Customer No. 33354

(vi) means electrically activatable for generating a sound audible to the user, and

(vii) means electrically connected to said timing circuit and said sound generating means for electrically charging in response to said beam of laser light being generated and for electrically discharging and thereby electrically activating said sound generating means in response to termination of generation of said beam of laser light.

18. (original) The device of claim 17 wherein said housing further has a cradle mounted to and projecting outwardly from said exterior of said housing for releasably securing said wand thereto, said cradle defining an annular slot open at opposite ends such that said tubular wand can be removably and slidably placed through said slot in a relatively tight-fitting relationship with said cradle and thereby retained by said cradle in a storage position spaced from and alongside said housing.

19. (original) The device of claim 17 wherein said housing further has a clip mounted to said exterior of said housing for releasably securing said housing to an article of clothing worn by the user.

20-34 (cancelled)

35. (previously presented) A hand-held laser light generator device for use in medical therapy, said device comprising:

Response to Office Action
SN 10/008393
Customer No. 33354

(a) a wand in the form of a substantially elongated hollow tube;

(b) means attached to said wand for generating a beam of laser light in the red color spectrum;

(c) an optical arrangement attached to said wand for transforming the generated beam of laser light into a line of laser light at a desired location on the surface of the patient's skin;

(d) means for supplying electrical power to said laser beam generating means; and

(e) means for electrically interconnecting said laser beam generating means and said electrical power supplying means.

36. (previously presented) The device of claim 35 wherein the tube defines an interior cavity and is capable of being retained in a hand of a user and freely moved relative to the surface of the skin of a patient to receive the medical therapy; and the means for generating a beam of laser light is mounted in said interior cavity of said wand.

37. (previously presented) The device of claim 35 wherein the electrical power supplying means is a battery.

Response to Office Action
SN 10/008393
Customer No. 33354

38. (previously presented) The device of claim 35 further comprising a means on said wand for controlling a period of time said beam of laser light is generated.
39. (previously presented) The device of claim 38 further comprising a means electrically interconnected to said means for controlling a period of time for informing the user that the laser light is no longer being generated.
40. (previously presented) The device of claim 35 wherein said wand further has a clip mounted to said exterior of said wand for releasably securing said wand to an article of clothing worn by the user.
41. (previously presented) A hand-held laser light generator device for use in medical therapy, said device comprising:
- (a) a wand in the form of a substantially elongated hollow tube defining an interior cavity;
- (b) means mounted in said interior cavity of said wand for generating a beam of laser light;
- (c) an optical arrangement mounted in said interior cavity for receiving the generated beam of laser light and for transforming the generated beam of laser light into a line of laser light in the red color spectrum at a desired location on the surface of the patient's skin;
- (d) means disposed in said interior cavity for supplying electrical power to said laser beam

Response to Office Action
SN 10/008393
Customer No. 33354

generating means; and

(e) means for electrically interconnecting said laser beam generating means and said electrical power supplying means.

42. (previously presented) The device of claim 41 wherein the electrical power supplying means is a battery.

43. (previously presented) The device of claim 41 further comprising a means on said wand for controlling a period of time said beam of laser light is generated.

44. (previously presented) The device of claim 43 further comprising a means electrically interconnected to said means for controlling a period of time for informing the user that the laser light is no longer being generated.

45. (previously presented) The device of claim 41 wherein said wand further has a clip mounted to said exterior of said wand for releasably securing said wand to an article of clothing worn by the user.

46. (previously presented) A hand-held laser light generator device for use in medical therapy, said device comprising:

(a) a wand in the form of a substantially elongated hollow tube defining an interior cavity

Response to Office Action
SN 10/008393
Customer No. 33354

and capable of being retained in a hand of a user and freely moved relative to the surface of the skin of a patient to receive the medical therapy;

(b) means mounted in said interior cavity of said wand for generating a beam of laser light in the red color spectrum;

(c) an optical arrangement mounted in said interior cavity of said wand for receiving the red color spectrum generated beam of laser light from said generating means and for transforming the generated beam of laser light into a substantially planar beam of laser light disposed externally of said wand for producing a line of laser light in the red color spectrum at a desired location on the surface of the patient's skin and with said line of laser light being visible to the user as said wand is held and freely moved by the user in a spaced relationship from and out of contact with the patient;

(d) a housing defining an interior chamber and having an exterior;

(e) means disposed in said interior chamber of said housing for supplying electrical power to said laser beam generating means;

(f) means for electrically interconnecting said laser beam generating means and said electrical power supplying means; and

Response to Office Action
SN 10/008393
Customer No. 33354

(g) means on said housing for controlling a period of time said beam of laser light is generated.

47. (previously presented) The device of claim 46 further comprising a means electrically interconnected to said means for controlling a period of time for informing the user that the laser light is no longer being generated.

48. (previously presented) The device of claim 46 wherein the electrical power supplying means is a battery.

49. (previously presented) The device of claim 46 wherein said wand further has a clip mounted to said exterior of said wand for releasably securing said wand to an article of clothing worn by the user.

50. (previously presented) A hand-held laser light generator device for use in medical therapy, said device comprising:

(a) a wand in the form of a substantially elongated hollow tube and capable of being retained in a hand of a user and freely moved relative to the surface of the skin of a patient to receive the medical therapy;

(b) a laser disposed in said wand for generating a beam of laser light for providing the medical therapy; and

Response to Office Action
SN 10/008393
Customer No. 33354

(c) an optical arrangement disposed in said wand for receiving the beam of laser light from the laser and for transforming the beam of laser light into a line of laser light at a desired location on the surface of the patient's skin and with said line of the laser light being visible to the user as said wand is held and freely moved by the user during said therapy.

51. (previously presented) The device of claim 50 further comprising an electrical circuit for controlling a period of time said beam of laser light is generated.

52. (previously presented) The device of claim 51 wherein said electrical circuit further comprises switches for controlling a period of time said beam of laser light is generated

53. (previously presented) The device of claim 51 wherein said electrical circuit further comprises push buttons for controlling a period of time said beam of laser light is generated.

54. (previously presented) The device of claim 51 wherein said electrical circuit is disposed in a housing operably connected to said wand, wherein the electrical circuit further comprises push buttons activatable between on and off positions and capable of setting multiple periods of time the laser is on; wherein the buttons are accessible at the exterior of said housing.

Response to Office Action
SN 10/008393
Customer No. 33354

55. (previously presented) The device of claim 51 wherein said electrical circuit is disposed in a housing operably connected to said wand, wherein the electrical circuit further comprises a start switch button activatable between on and off positions and capable of selecting multiple periods of time the laser is on; wherein the push buttons are accessible at the exterior of said housing.
56. (previously presented) The device of claim 51 wherein said electrical circuit further comprises a first push button for activating the laser and a second push button for deactivating the laser.
57. (previously presented) The device of claim 50 wherein the optical arrangement comprises a mechanical arrangement.
58. (previously presented) The device of claim 50 wherein the optical arrangement comprises two or more optical devices.
59. (previously presented) The device of claim 50 wherein the optical arrangement consists of a single beam shaping lens.
60. (previously presented) The device of claim 50 wherein the laser is a semiconductor laser diode.

Response to Office Action
SN 10/008393
Customer No. 33354

61. (previously presented) The device of claim 50 wherein the device further comprises a battery operably connected to said laser for supplying electrical power to said laser.
62. (previously presented) The device of claim 35 further comprising a housing operably connected to the wand wherein said housing further has a clip mounted to said exterior of said housing for releasably securing said housing to an article of clothing worn by the user.
63. (previously presented) The device of claim 41 further comprising a housing operably connected to the wand wherein said housing further has a clip mounted to said exterior of said housing for releasably securing said housing to an article of clothing worn by the user.
64. (previously presented) The device of claim 46 wherein said housing further has a clip mounted to said exterior of said housing for releasably securing said housing to an article of clothing worn by the user.